

Dr. Fixit LW+ Super



LIQUID PLASTICIZING & WATERPROOFING COMPOUND

Dr. Fixit LW+ Super is specially formulated integral liquid waterproofing compound composed of surface active plasticising agents, polymer & additives specially formulated to work with M-Sand (Manufactured Sand). It is used as admixture for site-mixed cement concrete, mortar & plastering. It makes concrete cohesive and prevent segregation & facilitates excellent retention of workability. In addition, to lower water cement ratio it eliminates chances of bleeding and shrinkage cracks in mortar.

Typical Applications

- RCC Slab
- Waterproofing of concrete and cement sand mortars
- Internal and External plastering

Features

- **Delays Corrosion** - Makes concrete more cohesive, hence protects steel better against corrosion.
- **Improves workability with M-Sand** - Facilitates easy placing and good compaction of mixed cement concrete and plaster mortar/ screed specially made with M-Sand.
- **Waterproof concrete & mortar** - Increases durability by improving waterproofing of concrete.
- **Increase strength and durability** - The setting time and compressive strength of the concrete remains within the specification limits.
- **Compatibility** - Being a liquid, easily dispersible & compatible with concrete/mortar mixes.
- **Shrinkage** - Reduces shrinkage crack development in plaster & concrete.

Packaging

- 1, 5, 10, 20 & 50 litre

Method of Application

- Charge cement & aggregates to concrete mixer as per the mix design, mix in dry state for 1-2 minutes.
- Start addition of 75-80% mixing water & mix for 2-3 minutes.
- Dr. Fixit LW+ Super is added as per the recommended dosage into the remaining mixing / gauging water, then add to concrete mixer & mix for another 2 minutes.
- Place the concrete or apply plaster, as needed.
- Cure the applied mortar or concrete as per good construction practices.

Precautions & limitations

- Do not add Dr. Fixit LW+ Super directly to dry cement & aggregate mix.
- Maintain water-cement ratio as low as possible.
- Do not increase the dosage of Dr. Fixit LW+ Super than the recommendation.



Technical Information

Properties	Specification	Results
Appearance		Pink Liquid
Specific gravity @ 25°C		1.04 - 1.09
Non Volatile content		15 - 16.5%
pH Value @ 30 deg		13
Chloride content	IS: 2645: 2003	Max 2.00 %
Water permeability	IS: 2645: 2003	Passes
Compressive strength N/mm ²	IS: 2645: 2003	As per the standard

Dosage

200 ml per 50 kg bag of cement.

Shelf Life

Shelf life is 24 months from the date of manufacturing. Store in a cool & dry place in unopened condition.

Health and Safety

- Use rubber hand gloves & safety goggles, while using Dr. Fixit Pidiproof LW+.
- In case of contact with skin, wash with plenty of water.
- Keep out of reach of children

Other Products Categories available

Dr. Fixit brings you the widest range of Construction Chemicals



Pidilite Industries Limited
 Construction Chemicals Division
 Ramkrishna Mandir Road, Post Box No. 17411
 Andheri (E) Mumbai 400059 INDIA
 Tel +91-22-2835 7000 • Fax +91-22-2835 7008
 www.drfixit.co.in • info.drfixit@pidilite.com
 Dr. Fixit Advice Centre (Toll Free No.) 1800 209 5504

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.