



Dr. Fixit Rust Remover

LIQUID FOR CLEANING RE-BARS & STEEL SURFACES

Description

Dr. Fixit Rust Remover is based on chloride free chemical & additive solution in water. it is used as rust remover which effectively cleans rust from steel surfaces, before application of any protective coating.

Areas of Application

- On re-bars during repairs to reinforced concrete structures.
- Maintenance of mild steel structures like tanks, water pipelines, shuttering plates and other corroded steel surfaces.

Features & Benefits

- **Ease of application** - Ready to use, easily applicable by brush.
- **Penetration & effect** - Effective rust removal even from areas difficult to reach & penetrate.
- **Chloride free** - Contains no chloride hence no chance of enhancing further corrosion.
- **Economical** - Cost effective because of good coverage.

Method of Application

1 SURFACE PREPARATION

- In case of heavy rusting of steel reinforcement, M.S. pipelines, M.S. plates or any other M.S. surface, remove the loose rust by wire brushing, chipping, hammering or grinding so that majority of rust scale is removed.

2 APPLICATION

- Apply Dr. Fixit Rust Remover on affected surface by using cotton waste swab or by brush application. Leave the surface to react with Dr. Fixit Rust Remover for at least 15 to 30 minutes.
- The rusty surface will change its colour to original blackish steel, remove the same with cotton cloth.
- Then remove the loose rust particles by scrubbing or simple dusting with the brush.
- Wash the steel surface with water jetty to remove all the acidic residue left on the bar, and clean with cotton cloth.

3 FINISH

- When applied over corroded reinforcement steel, wash the surface with clean water before taking up further work of repairs.

Precautions & Limitations

- Dr. Fixit Rust Remover is acidic in nature, when applied to clean the rusted rebars. Ensure that traces of acid are removed completely by washing with a water jet, before applying coatings or primers.
- For thorough removal of rust and cleaning steel bar to SA 2 1/2 standards, sweep blasting is recommended.

Technical Information

PROPERTIES	RESULTS
Appearance	Water consistency liquid
Colour	Brown
PH	Acidic
Sp. gravity	1.20 +/- 0.03



Coverage / Usage

Approximately 15 to 20 m² / litre

Packaging

500 ml & 1 litre

Shelf Life

Shelf life is 24 months from the date of manufacturing in unopened condition. Store at cool & dry place away from sunlight & naked flames.

Health & Safety Precautions

- As with all chemical products, caution should always be exercised.
- Use of safety hand gloves is recommended.
- Treat any contact to the skin or eyes with fresh water immediately.
- Should any of the products be accidentally swallowed, do not induce vomiting but call for medical assistance immediately.

Other Products Categories available

Dr. Fixit brings you the widest range of Construction Chemicals



Pidilite Industries Limited
Construction Chemicals Division
Ramkrishna Mandir Road, Post Box No. 17411
Andheri (E) Mumbai 400059 INDIA
Tel +91-22-2835 7000 • Fax +91-22-2835 7008
www.drfixit.co.in • info@drfixit.co.in

Dr. Fixit Advice Centre (Toll Free No.) 1800 209 5504

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.