

# Dr. Fixit Triflex Glass Primer



## SINGLE COMPONENT GLASS PRIMER

### Description

Dr. Fixit Triflex Glass Primer is single -component low viscous transparent primer for various glass surfaces to be used in conjunction with Dr. Fixit Triflex waterproofing products.

### Areas of Application

Dr. Fixit Triflex Glass Primer is used as a primer to be used on unpolished glass substrates under Dr. Fixit Triflex ProDetail & Dr. Fixit Triflex Protect range of detailing and waterproofing products.

### Features & Benefits

- Single Component
- Fast-drying
- Faster recoating time
- Low viscosity

### Method of Application

- Dr. Fixit Triflex Glass Primer can be applied at substrate and ambient temperatures between 0 °C and +35 °C.

### Application of Primer

- Before applying the product, stir or shake the contents until homogeneous. Apply a thin layer of Dr. Fixit Triflex Glass Primer using a short-pile roller or a brush consumption of 40-60 ml/m<sup>2</sup>. Make sure the application layer is not too thick. Once the Dr Fixit Triflex Metal Primer has fully hardened, it can be further processed.

### Preparation of the substrate

- The substrate must be sound

### Technical Properties

PROPERTIES	TYPICAL VALUES
Colour	Transparent
Density	0.75-0.85 g / cc
Viscosity	3-10 cps
Recoating time	10 mins @30 °C
Can be Recoated until	2 hrs @30 °C

### Recommended Coverage

Approx. 40-60 ml/m<sup>2</sup> in single coat.

The specified consumptions apply only to smooth, even surfaces. Special allowances must be made for unevenness, roughness and porosity.

### Packaging

Dr. Fixit Triflex Glass Primer - 750 ml Metal can ( Transparent colour).

### Storage

Can be stored unopened and unmixed for approx. 24 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.



### Shelf Life & Storage

Shelf life is 24 months. To be stored unopened and unmixed in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site. Storage temperature: 8°C-35°C

### Safety & Handling

During application wear protective clothing, gloves and eye goggles during application. Avoid product to contact eyes and skin. Skin Contact - Wash immediately with plenty of clean water. Eye contact - In the event of eye contact splash plenty of clean water immediately and seek medical advice.

### Other Products Categories available

Dr. Fixit brings you the widest range of Construction Chemicals



#### Pidilite Industries Limited

Construction Chemicals Division  
 Ramkrishna Mandir Road, Post Box No. 17411  
 Andheri (E) Mumbai 400059 INDIA  
 Tel +91-22-2835 7000 • Fax +91-22-2835 7008  
 www.drfixit.co.in • info.drfixit@pidilite.com  
 Dr. Fixit Advice Centre (Toll Free No.) 1800 209 5504

**DISCLAIMER** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.